

# B125CS NEW



Resin • Flat head

Economical

- Good scratch and smear resistance
- High sensitivity
- High resolution
- Suitable for a variety of applications
- Applicable to a wide range of paper and film materials

#### PRINTING PROPERTIES

	Non top-coated paper	Top-coated paper	PP	PET
Compatibility	×	$\varnothing$	$ \emptyset $	Ø
Image density	-	1.69	1.76	1.77

### RIBBON PROPERTIES

Total ribbon thickness: < 9 μm</li>

• Polyester film thickness: 4.7μm ± 0.3μm

• Tearing resistance: > 200N/mm<sup>2</sup>

**Factory** 

Storage

Application

Product label

圖

Retail

Logistics label

Chemical



Hospital

## **CERTIFICATES/ DIRECTIVES**





# **GENERAL CONDITION**

Usage conditions: 5 to 35°C at 30 to 85% of relative humidity.

Storage conditions: Keep indoor avoiding high temperature, high humidity,

direct sunlight.


Storage life: 12 months after slitting day.



#### PRINTED IMAGE DURABILITY

TESTS	RESULT
Scratch resistance	ANSI 3.0B or more
1500 back and forwards with a rub tester	
Smear resistance + heat 100°C	ANSI 3.0B or more
Smear with cardboard (weight 1kg - 50 back & forwards)	
Water resistance	ANSI 3.5A or more
Alcohol resistance	ANSI C or more
Others	No Blocking and satisfies recording characteristics and compatibility after storage of 40°C for 72 hours

# **B125CS CHARACTERISTICS**



These performances are for guidance only. Results are obtained with adapted receiving material and optimum print conditions. (Ricoh test method)

#### RICOH VIETNAM COMPANY LTD.

F17, E.Town Central, 11 Doan Van Bo, Ward 13, District 4, HCM City

Tel: +84 28-3528-5252 Fax: +84 28-3636-7211

Email: thermal@ricoh.com.vn Website: https://ricoh.com.vn/products/thermal



<sup>\*</sup> Specifications are subjected to change without notice.

<sup>\*</sup> The color(s) of the actual product may vary from the color(s) shown in this datasheet